

ColdFAST

COLDFAST C 128 CRYO






Technical specifications

ColdFAST

COLDFAST C 128 CRYO



COLDFAST C 128 CRYO

Model	Type of Construction	Chest
	Capacity (l)	128
	Inner Dimensions (W x D x H) mm	510 x 460 x 540
	Outer Dimensions (W x D x H) mm	1665 x 1000 x 1115
	Package Dimensions (W x D x H) mm	1815 x 1085 x 1304
	Net / Gross Weight (kgs)	390 / 529
Performance	Cooling Performance (°C)	-145
	Temperature Range (°C)	-110 ~ -150
	Ambient Temperature (°C)	16 ~ 32
	Climate Class	N
	Sound Level (dB(A))	68
	Controller	Microprocessor
Refrigeration	Display	Digital Display
	Compressor	1 pcs
	Cooling Mode	Direct Cooling
	Defrost Mode	Manual
	Refrigerant	Mixture gas
	Insulation Thickness (mm)	205
Construction	External Material	High quality Steel plates with spraying
	Inner Material	Stainless Steel
	Foaming Lid	2
	Casters	6
	Access Test Port	1 pcs. Ø 40 mm
	Data Logging / Time / Duration	Printe / Record Every 20 Minutes / 7 Days
	Backup Battery	Yes
Alarm	Temperature	High / Low Temperature, High Ambient Temperature
	Electrical	Power Failure, Low Battery
	System	Sensor and System Failure, Main Board Communication Error, Condenser Overheating
Electrical Data	Power Supply (V/HZ)	380 / 50-60
	Rated Power (W)	4000
	Current Consumption (KWh/24h)	70
	Electrical Current (A)	20,69
Accessories	Standard	Chart-Recorder, CO ₂ -Backup-System

The model, parameters and performance specified in this brochure may be changed without prior notice because of product upgrading.
There may be differences between the product images shown in this brochure and the actual products. When you are buying any product, please check the actual product.